EAST Browser - L27: (26) string and t... | US 6203556 | Tag: S | Doc: 5/26 (SORTED) | "Full" 1/21 (Total images 21) | Front Page

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image Doc
1	US 5673355 A		USPAT	19970930	52	US 56733
2	US 5912317 A		USPAT	19990615	11	US 59123
3	US 6090905 A		USPAT	20000718	14	US 60909
4	US 6114491 A		USPAT	20000905	15	US 61144
5	US 6203556 B1		USPAT	20010320	21	US 62035
6	US 6235045 B1		USPAT	20010522	35	US 62350
7	US 6245438 B1		USPAT	20010612	16	US 62454
8	US 6274527 B1		USPAT	20010814	6	US 62745
9	US 6319275 B1		USPAT	20011120	22	US 63192
10	US 6369171 B1		USPAT	20020409	17	US 63691
11	US 6379814 B1		USPAT	20020430	16	US 63798
12	US 6379366 B1		USPAT	20020430	27	US 63793
13	US 6423086 B1		USPAT	20020723	35	US 64230
14	US 6432128 B1		USPAT	20020813	20	US 64321
15	US 6432121 B1		USPAT	20020813	81	US 64321
16	US 6436118 B1		USPAT	20020820	25	US 64361
17	US 6486296 B1		USPAT	20021126	8	US 64862
18	US 6514271 B2		USPAT	20030204	21	US 65142
19	US 6530934 B1		USPAT	20030311	11	US 65309
20	US 6551326 B1		USPAT	20030422	10	US 65513
21	US 6558408 B1		USPAT	20030506	20	US 65584
22	US 6635068 B1		USPAT	20031021	14	US 66350
23	US 6676672 B2		USPAT	20040113	21	US 66766
24	US 6733519 B2		USPAT	20040511	24	US 67335
25	US 6752822 B2		USPAT	20040622	9	US 67528
26	US 6830576 B2		USPAT	20041214	26	US 68305

US006203556B1

(12) **United States Patent**
Evans et al.

(10) **Patent No.: US 6,203,556 B1**
(45) **Date of Patent: *Mar. 20, 2001**

(54) **TRANSMYOCARDIAL REVASCULARIZATION SYSTEM AND METHOD OF USE**

(75) Inventors: **Douglas G. Evans**, Downingtown; **John E. Nash**, Chester Springs, both of PA (US)

(73) Assignee: **Kansey Nash Corporation**, Exton, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: 09/369,107

(22) Filed: Aug. 5, 1999

Related U.S. Application Data

(63) Continuation of application No. 08/958,788, filed on Oct. 29, 1997, now Pat. No. 5,980,548.

(51) Int. Cl.[7] A61B 17/34

(52) U.S. Cl. 606/185; 606/220

(58) Field of Search 606/185, 213, 606/119, 220, 7, 15; 623/3.11, 3.26, 11; 128/898

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,887,699 6/1975 Yates .

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

296 19 029 U 4/1997 (DE) .
196 45 153 A1 5/1998 (DE) .

(List continued on next page.)

OTHER PUBLICATIONS

Uchida et al., Angiogenic Therapy of Acute Myocardial Infarction by Intrapericardial Injection of Basic Fibroblast Growth Factor and Heparin Sulfate: An Experimental Study, American Heart Journal, 130:1182–1185, Dec. 1995.

(List continued on next page.)

Primary Examiner—Kevin Truong
(74) *Attorney, Agent, or Firm*—Caesar, Rivise, Bernstein, Cohen & Pokotilow, Ltd.

(57) **ABSTRACT**

A transmyocardial revascularization system including a plurality of inserts formed of a material to elicit a healing response in tissue of the myocardium and deployment instruments and associated components for deploying the inserts into the wall of the myocardium. The inserts are arranged to be disposed within respective lumens or channels in the wall of the myocardium. The inserts can take various forms, e.g., be solid members, tubular members, or porous members, and may be resorbable, partially resorbable or non-resorbable. In some embodiments the inserts are arranged to be left in place within the channels in the wall of the myocardium to result in distal lumens which enable blood to flow therethrough and into contiguous capillaries. The deployment instruments are arranged to pierce the tissue of the myocardium from either the endocardium or the epicardium to insert the inserts into the myocardium, depending on the particular deployment instrument used. The deployment instruments may make use of a stabilizing device to stabilize them during the procedure of inserting the inserts into the myocardium. A controller may also be provided as part of the system to coordinate the operation of the deployment instrument with the cardiac cycle. The formation of the lumens can be achieved either by the inserts or by some other means, such as a piercing tip or an energy applicator forming a portion of the instrument. The inserts may include one or more of pharmaceuticals, biologically active agents, radiopaque materials, etc.

19 Claims, 10 Drawing Sheets



See Fig. 9F

EAST Browser - L39: (795) (string or t... | US 4961740 | Tag: S | Doc: 137/795 (SORTED) | "Full" 1/29 (Total images 29) | Front Page

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image D
118	US 4863460 A		USPAT	19890905	9	US 4863
119	US 4877020 A		USPAT	19891031	6	US 4877
120	SU 1519684 A		DERWEN	19891107	1	1990-15
121	US 4881938 A		USPAT	19891121	8	US 4881
122	US 4881937 A		USPAT	19891121	7	US 4881
123	EP 358345 A1	A1, B1	EPO	19900314	6	EP 3583
124	EP 358345 A	A1, B1	DERWEN	19900314	6	EP 3583
125	US 4911716 A		USPAT	19900327	17	US 4911
126	US 4917756 A		USPAT	19900417	14	US 4917
127	US 4919674 A		USPAT	19900424	7	US 4919
128	US 4919666 A		USPAT	19900424	9	US 4919
129	US 4928690 A		USPAT	19900529	24	US 4928
130	US 4932870 A		USPAT	19900612	8	US 4932
131	US 4932868 A		USPAT	19900612	12	US 4932
132	US 4935030 A		USPAT	19900619	6	US 4935
133	US 4936853 A		USPAT	19900626	7	US 4936
134	US 4938762 A		USPAT	19900703	12	US 4938
135	JP 02218361 A		JPO	19900831	5	JP 0221
136	US 4955916 A		USPAT	19900911	5	US 4955
137	US 4961740 A		USPAT	19901009	29	US 4961
138	US 4963502 A		USPAT	19901016	10	US 4963
139	US 4968317 A		USPAT	19901106	18	US 4968
140	US 4981481 A		USPAT	19910101	10	US 4981
141	US 4981475 A		USPAT	19910101	6	US 4981
142	US 4988299 A		USPAT	19910129	4	US 4988
143	EP 412845 A1	A1, B1	EPO	19910213	11	EP 4128
144	EP 412845 A	A1, B1	DERWEN	19910213	11	EP 4128
145	WO 9101691 A1		EPO	19910221	34	WO 9101
146	US 4997447 A		USPAT	19910305	6	US 4997
147	US 5002661 A		USPAT	19910326	18	US 5002
148	US 5002567 A		USPAT	19910326	6	US 5002
149	US 5009664 A		USPAT	19910423	6	US 5009
150	US 5011494 A		USPAT	19910430	26	US 5011
151	US 5013242 A		USPAT	19910507	5	US 5013
152	US 5016645 A		USPAT	19910521	9	US 5016
153	US 5019435 A		USPAT	19910528	13	US 5019
154	US 5021064 A		USPAT	19910604	32	US 5021
155	US 5026373 A		USPAT	19910625	11	US 5026
156	US 5030194 A		USPAT	19910709	13	US 5030
157	EP 437401 A	A1, B1	DERWEN	19910717	7	EP 4374
158	US 5043778 A		USPAT	19910827	11	US 5043
159	US 5055104 A		USPAT	19911008	9	US 5055
160	US 5059654 A		USPAT	19911022	51	US 5059

United States Patent [19]

Ray et al.

[11] Patent Number: **4,961,740**

[45] Date of Patent: **Oct. 9, 1990**

[54] **V-THREAD FUSION CAGE AND METHOD OF FUSING A BONE JOINT**

[75] Inventors: Charles D. Ray, Deephaven; Eugene A. Dickhudt, New Brighton, both of Minn.

[73] Assignee: Surgical Dynamics, Inc., Alameda, Calif.

[21] Appl. No.: 259,031

[22] Filed: Oct. 17, 1988

[51] Int. Cl.[5] A61F 5/04; A61F 2/28

[52] U.S. Cl. 606/61; 606/86; 623/16

[58] Field of Search ..... 128/92 YJ, 92 C, 92 CA, 128/92 UP, 92 YP, 92 YZ; 623/16, 17, 18

[56] References Cited

U.S. PATENT DOCUMENTS

Re. 31,863	4/1985	Rosa	623/18
2,537,070	1/1951	Longfellow	128/92 YJ
3,720,959	3/1973	Helm	623/16
3,783,800	1/1974	Barnett et al.	128/92 YZ
4,059,115	11/1977	Jamshidi et al.	128/92 YJ
4,495,226	1/1985	Belykh et al.	128/92 YZ
4,501,269	2/1985	Bagby	128/92 YJ
4,522,200	6/1985	Stednitz	128/92 YZ
4,599,085	7/1986	Doty	128/92 R
4,657,550	4/1987	Daher	128/92 YM
4,673,972	7/1987	Tornier	128/92 VP

FOREIGN PATENT DOCUMENTS

2257729 12/1974 France .

Primary Examiner—Robert A. Hafer
Assistant Examiner—Kerry Owens
Attorney, Agent, or Firm—Fliesler, Dubb, Meyer & Lovejoy

[57] **ABSTRACT**

A fusion cage 10 includes a cage body defining an internal cavity with an inner surface and an outer surface. The outer surface defines a helical thread 12 comprised of a plurality of ribs which define valleys 14 therebetween. Located in the valleys 14 are perforations 13 which provide communication between the outer surface and the interior cavity. Thus, when the fusion cage 10 is mated to a bone structure and the internal cavity is packed with bone chips or other bone-growth-inducing substances, there is immediate contact between the bone structure and the bone chips through the perforations 13.

34 Claims, 1 Drawing Sheet



EAST Browser - L39: (795) (string or t... | US 4961740 | Tag: S | Doc: 137/795 (SORTED) | "Full" 5/29 (Total Images 29) | Specifications

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image D
118	US 4863460 A		USPAT	19890905	9	US 4863
119	US 4877020 A		USPAT	19891031	6	US 4877
120	SU 1519684 A		DERWEN	19891107	1	1990-15
121	US 4881938 A		USPAT	19891121	8	US 4881
122	US 4881937 A		USPAT	19891121	7	US 4881
123	EP 358345 A1	A1, B1	EPO	19900314	6	EP 3583
124	EP 358345 A	A1, B1	DERWEN	19900314	6	EP 3583
125	US 4911716 A		USPAT	19900327	17	US 4911
126	US 4917756 A		USPAT	19900417	14	US 4917
127	US 4919674 A		USPAT	19900424	7	US 4919
128	US 4919666 A		USPAT	19900424	9	US 4919
129	US 4928690 A		USPAT	19900529	24	US 4928
130	US 4932870 A		USPAT	19900612	8	US 4932
131	US 4932868 A		USPAT	19900612	12	US 4932
132	US 4935030 A		USPAT	19900619	6	US 4935
133	US 4936853 A		USPAT	19900626	7	US 4936
134	US 4938762 A		USPAT	19900703	12	US 4938
135	JP 02218361 A		JPO	19900831	5	JP 0221
136	US 4955916 A		USPAT	19900911	5	US 4955
137	US 4961740 A		USPAT	19901009	29	US 4961
138	US 4963502 A		USPAT	19901016	10	US 4963
139	US 4968317 A		USPAT	19901106	18	US 4968
140	US 4981481 A		USPAT	19910101	10	US 4981
141	US 4981475 A		USPAT	19910101	6	US 4981
142	US 4988299 A		USPAT	19910129	4	US 4988
143	EP 412845 A1	A1, B1	EPO	19910213	11	EP 4128
144	EP 412845 A	A1, B1	DERWEN	19910213	11	EP 4128
145	WO 9101691 A1		EPO	19910221	34	WO 9101
146	US 4997447 A		USPAT	19910305	6	US 4997
147	US 5002661 A		USPAT	19910326	18	US 5002
148	US 5002567 A		USPAT	19910326	6	US 5002
149	US 5009664 A		USPAT	19910423	6	US 5009
150	US 5011494 A		USPAT	19910430	26	US 5011
151	US 5013242 A		USPAT	19910507	5	US 5013
152	US 5016645 A		USPAT	19910521	9	US 5016
153	US 5019435 A		USPAT	19910528	13	US 5019
154	US 5021064 A		USPAT	19910604	32	US 5021
155	US 5026373 A		USPAT	19910625	11	US 5026
156	US 5030194 A		USPAT	19910709	13	US 5030
157	EP 437401 A	A1, B1	DERWEN	19910717	7	EP 4374
158	US 5043778 A		USPAT	19910827	11	US 5043
159	US 5055104 A		USPAT	19911008	9	US 5055
160	US 5059654 A		USPAT	19911022	51	US 5059

thread has from 3 to 8 turns per cm. A smaller turn ratio may result in an undesirably large thread depth, penetrating too deeply into the cancellous bone. A larger turn ratio may unduly restrict the size of the perforations.

The novel V-thread fusion basket can be implanted for fixing adjacent bony structures by the following method:

(a) forming in said bony structures a bore with a female thread that penetrates into their cancellous regions,

(b) forming a rigid, perforate, cylindrical basket to have an external, substantially continuous helical V-thread that can mate with said female thread,

(c) screwing the basket into said threaded bore, and

(d) packing the basket with bone-inducing substance.

When the bore to be formed in step (a) is to extend between adjacent vertebrae, there should be prior to step (a) the added step of spreading the vertebrae apart, preferably in a manner that maintains their parallelism, the fusion basket is implanted in pairs on opposite sides of the disc space.

The novel fusion basket should have a modulus of elasticity approximating that of the recipient bone, thus permitting it to flex along its length, consequently minimizing stresses at the bony interface between the graft and recipient bone. Although a fusion basket of substantially lower modulus of elasticity would provide the same desirable result, it might not have adequate structural strength.

The bore into which the V-thread fusion basket is to be inserted preferably is tapped by hand, using a slow motion to ensure against burning the bone. This freshens the bone margins of the bore so that if any bone had been burned by drilling to form the bore, it is now cut away slowly by hand. The tapping process is quite safe, in that the surgeon can feel the progress of the technique.

The V-thread fusion basket preferably is screwed by hand into the threaded bore, again permitting the surgeon to feel if the resistance is too great and that rethreading of the bore might be required. In contrast, a bone dowel typically is driven into a bore using a hammer, and in order to guard against an overly tight fit, the surgeon listens to the sound of the striking hammer and also monitors the degree of resistance.

When using the novel fusion basket to create bone ingrowth between adjacent vertebrae, the fusion basket should be implanted in pairs on opposite sides of the disc space. Each is held in place by its V-thread, biting into female threads that penetrate into the cancellous bone of the interposed vertebral bodies. Gravity, muscle pull and elastic recoil of the spread (or stretched) outer disc annius together exert force against each of the fusion baskets. Thus the fusion baskets are held in place by compression forces between the adjacent vertebrae.

To prevent distraction forces from possibly dislodging the fusion baskets, e.g., when the patient forward flexes, thus separating the posterior margins of the adjacent vertebrae, the dorsal processes may be tied or wrapped together. By another technique, screws placed through the appropriate facet jackets limit both flexion and extension motions.

A novel interbody spreader in the form of a scissors jack has been developed to maintain a desirable parallel attitude between the adjacent vertebrae while the bore is drilled and then tapped by a novel instrument. Another instrument that has been developed for use in the implantation of the novel fusion basket is a tapping instrument for forming helical threads in a bore in recipient bone. This novel tapping instrument comprises

a hollow cylindrical shaft having a handle at one end and an external thread which is formed at the other end with at least one scallop that exposes a cutting edge, and

a pilot rod that slidably fits into said bore, projects beyond said other end of the hollow shaft, and is formed with a central recess that communicates with the scallop in the hollow shaft and provides a reservoir for detritus removed by said cutting edge, thus permitting the detritus to be carried away by removing the pilot rod from the hollow shaft. The portion of the pilot rod that projects beyond said other end of the hollow shaft preferably is threaded to carry detritus upwardly to the reservoir.

When using the novel tapping instrument to form female threads for an interbody fusion, the hollow shaft should have an odd number of scallops and cutting edges, preferably three, because an odd number provides more equal removal of recipient bone on both sides of the bore than would an even number.

The novel tapping instrument and a novel wrench are illustrated in the drawing that also illustrates two V-thread fusion baskets of the invention.

THE DRAWING

In the drawing, all figures of which are schematic,

FIG. 1 is an exploded isometric view of a first V-thread fusion basket of the invention and two perforated end caps;

FIG. 2 is an isometric view illustrating the formation of a body that can be cut to form a series of second V-thread fusion baskets of the invention;

FIG. 3 is an isometric view of a tap (partly cut away to reveal details of construction) for forming female threads in bores into which a V-thread fusion basket is to be inserted; and

FIG. 4 is an isometric view of a wrench for screwing a V-thread fusion basket into a threaded bore.

The fusion basket 10 of FIG. 1 was formed from a solid steel cylinder by drilling eight small, equally spaced holes 11 in the axial direction, each hole being centered on a circle concentric with the axis of the cylinder. Then a large hole was drilled centered on the axis and having a radius substantially identical to that of the aforementioned circle. A V-thread 12 was then machined in the external surface of the cylinder, thus opening through that surface a perforation 13 extending through the rounded valley 14 of the V-thread at each crossing of the valley and one of the small holes 11. A screw thread 15 was then machined in the internal surface of the fusion basket to threadably receive an end cap 16 that has apertures 18 similar to those of a salt shaker. Snap-on end caps would also be useful.

In making a fusion basket by the technique described in the preceding paragraph, the small holes 11 could be enlarged to intersect each other, thus making it unnecessary to drill a central hole. Enlarged small holes would result in larger perforations 13.

Referring to FIG. 2, a series of fusion baskets can be made from a plurality of rods 22 of rectangular cross-section that can be continuously extruded and fed into each of eight keyways 23 in the surface of a mandrel 24. Simultaneously, a rod 26 of triangular cross-section is extruded, wrapped helically around the rectangular rods 22, and soldered or welded to each of the rectangu-

ter rods 22 at every crossing to provide an external V-thread. Upon emerging from the keyways, the resulting body is cut into individual fusion baskets each of which has a perforation 28 between adjacent turns of the V-thread-forming rod 26 wherever it bridges a gap between adjacent rectangular rods 22.

A fusion basket identical to that of FIG. 2 can be made from a hollow cylinder by machining an external V-thread and broaching a plurality of rectangular internal keyways.

Each of the fusion baskets of FIGS. 1 and 2 could be made from a model by the lost wax process.

The tapping instrument 30 of FIG. 3 has a hollow cylindrical shaft 31 with a T-handle 32 at one end and an external thread 33 at the other end. Slidably received within the hollow shaft is a pilot rod 34, one end 35 of which protrudes beyond the hollow shaft 31 and slidably fits into a bore that has been drilled into the recipient bone. At the other end of the pilot rod is a knurled cap 35A. Projecting from the threaded end of the hollow shaft 31 are cutting teeth 36 that enlarge the bore to the minor diameter of the external thread 33 of the hollow shaft 31. The threaded end of the hollow shaft also is formed with three symmetrical scallops 37 (one shown) to expose a cutting edge 38 at the leading edge of the external thread 33, which cutting edge forms female bone threads in the bore upon rotation of the hollow shaft.

Detritus created by tapping instrument 30 is deposited through the scallops 37 into a reservoir provided by a central recess 39 in the pilot rod 34. The end 35 of the pilot rod which extends from the recess 39 into the bore has external threads which, when the threaded pilot rod 34 is turned, carry detritus upwardly to be deposited through the scallops into the reservoir.

Upon rotating the hollow shaft 31 to form female bone threads in the bore, the surgeon can feel increased back pressure when the reservoir becomes full and should grasp the knurled cap 35A to remove and clean out the pilot rod. If the gummy nature of the detritus were to prevent the pilot rod from being easily pulled out of the hollow shaft, the knurled cap 35A could be removed to permit the hollow shaft 31 to be unscrewed from the threaded bore, leaving the pilot rod in place. The pilot rod then serves as a guide if the bore has not yet been completely tapped and it is necessary to reinsert the hollow shaft to complete the tapping.

The wrench 40 of FIG. 4 has a cylindrical shaft 41 with a T-handle 42 at one end and an octagonal protuberance 44 at the other end. The corners of the protuberance 44 fit into recesses in the fusion basket to permit the fusion basket to be rotated by rotating the wrench. A spring-loaded ball 46 frictionally holds the protuberance in place when it is inserted into the fusion basket.

IMPLANTING THE FUSION BASKET

In order to implant the novel fusion basket between adjacent vertebrae, soft, collagenous disc material is first removed from the intervertebral space. A small window is created in the overlying laminas of each side, namely, standard laminotomies. The neural tissues, dural sac and nerves, are retracted medially. The intervertebral space is cleaned of disc material in a standard surgical fashion. If the disc space has narrowed as a result of degeneration, a scissors-jack type vertebral spreader or a hydraulically inflated bladder is inserted on one (the first) side inside the disc space and opened until the space approximates the normal. This may be confirmed by a lateral x-ray. The height of the disc space is measured on the x-ray so that the proper sizes of drills, tap, and fusion basket may be chosen.

The opposite (second) side of the same disc space is then addressed. The nerve tissues on the first side are relaxed and then retracted medialward on the second side. A pilot drill (e.g., 5 mm or 8 mm diameter depending upon distal space height) cuts a small channel in the face of each of the vertebrae, penetrating the interdiscal space to a depth of about 25 mm (the normal disc space is about 30 mm deep and 30 mm wide). A drill stop may be applied to the drill to prevent overboring the hole. A solid rod pilot is then inserted into the pilot hole and a pilot cutter (7 mm or 10 mm) is passed over it and brought downward to enlarge the pilot channels to slidably receive the pilot rod 35 of the tapping instrument 30 of FIG. 3. The cutting thread 33 (12 mm or 16 mm major diameter) cuts female bone threads through the opposing vertebral end plates and into both cancellous regions that will invite the ingrowth of new bone.

A V-thread fusion basket of the invention, with one end cap in place, is snapped onto the wrench 40 of FIG. 4 by which it is screwed by hand into the threaded intradiscal bore to its full depth. After removing the wrench, the basket is packed with bone chips or other bone-inducing substance, and the second end cap is applied to hold the bone chips securely in place.

After removing the vertebral spreader, the dura and nerves on the second side are relaxed and attention is once again directed to the first side which is drilled and tapped to receive a second fusion basket by the same procedure.

Over a period of several weeks, the bone from the vertebral bodies will grow through the perforations in the fusion baskets and unite with the bone-inducing substance inside them, creating a solid fusion.

It is believed that the novel fusion baskets will primarily be implanted by a posterior approach to the spine, although an anterior approach may be utilized, especially when applied to the cervical spine.

EXAMPLE 1

The fusion basket of FIG. 1 has been machined from a cylinder of surgically implantable stainless steel to have the following dimensions

diameter of starting cylinder	16 mm
length of cylinder	25 mm
diameter of each small hole 11	3 mm
diameter of circle on which holes 11 are centered	11.3 mm
diameter of central hole	11 mm
pitch of V-thread 12	2.5 mm/turn
angle at crown of thread 12	60°
fillet radius in valley of thread 12	0.4 mm
axial width of perforations 13	1.6 mm
circumferential breadth of perf. 13	2.6 mm
wrench engagement over interior of a cylinder, % of area perforated	25%

A V-thread fusion basket identical in appearance to one produced as in FIG. 2 can be made from a hollow cylindrical tube. After machining an external thread, a plurality of rectangular keyways are broached in the inner surface to form perforations through the valley of the thread. A continuous technique for making a novel fusion basket starts with a continuous helical spring made from a triangular rod such as the rod 26 used in FIG. 2, then welding or soldering the inner-facing sur-

EAST Browser - L39: (795) (string or t... | US 5336254 A | Tag: S | Doc: 225/795 (SORTED) | Format : KWIC

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image D
185	US 5161973 A		USPAT	19921110	6	US 5161
186	US 5167664 A		USPAT	19921201	5	US 5167
187	US 5171227 A		USPAT	19921215	8	US 5171
188	US 5176681 A		USPAT	19930105	12	US 5176
189	US 5185932 A		USPAT	19930216	28	US 5185
190	US 5196013 A		USPAT	19930323	7	US 5196
191	US 5195892 A		USPAT	19930323	5	US 5195
192	DE 4002171 C	A1, C2	DERWEN	19930325	8	DE 4002
193	EP 537101 A	A1, B1	DERWEN	19930414	9	EP 5371
194	WO 9306786 A1		EPO	19930415	20	WO 9306
195	US 5203788 A		USPAT	19930420	12	US 5203
196	US 5206840 A		USPAT	19930427	11	US 5206
197	SU 1818100 A		DERWEN	19930530	1	1994-31
198	US 5217811 A		USPAT	19930608	7	US 5217
199	US 5219361 A		USPAT	19930615	26	US 5219
200	US 5231996 A		USPAT	19930803	12	US 5231
201	US 5234434 A		USPAT	19930810	8	US 5234
202	US 5242445 A		USPAT	19930907	8	US 5242
203	US 5247597 A		USPAT	19930921	15	US 5247
204	US 5259398 A		USPAT	19931109	14	US 5259
205	US 5261913 A		USPAT	19931116	12	US 5261
206	US 5266352 A		USPAT	19931130	7	US 5266
207	US 5275603 A		USPAT	19940104	9	US 5275
208	US 5275563 A		USPAT	19940104	4	US 5275
209	US 5282781 A		USPAT	19940201	15	US 5282
210	EP 581667 A		DERWEN	19940202	8	EP 5816
211	US 5285131 A		USPAT	19940208	16	US 5285
212	RU 2007107 C		DERWEN	19940215	1	1994-27
213	US 5290310 A		USPAT	19940301	15	US 5290
214	US 5300115 A		USPAT	19940405	7	US 5300
215	US 5306308 A		USPAT	19940426	9	US 5306
216	US 5314500 A		USPAT	19940524	9	US 5314
217	US 5316476 A		DERWEN	19940531	13	US 5316
218	FR 2699398 A		DERWEN	19940624	8	FR 2699
219	US 5324306 A		USPAT	19940628	16	US 5324
220	US 5324199 A		USPAT	19940628	4	US 5324
221	US 5326263 A		USPAT	19940705	16	US 5326
222	US 5328372 A		USPAT	19940712	5	US 5328
223	US 5327906 A		USPAT	19940712	6	US 5327
224	US 5336268 A		USPAT	19940809	5	US 5336
225	US 5336254 A		USPAT	19940809	8	US 5336
226	US 5342367 A		USPAT	19940830	8	US 5342
227	US 5344422 A		USPAT	19940906	12	US 5344

Detailed Description Text - DETX (2):

FIG. 1 shows a bottom, plan view of an electrode according to the present invention. The electrode is provided with an insulative electrode pad 10, corresponding to the electrode pad illustrated in the above-cited U.S. Pat. No. 4,817,634, issued to Holleman et al. incorporated herein by reference in its entirety. The pad 10 is a generally planar structure fabricated of silicone rubber, polyurethane or other flexible insulative biocompatible plastic. It is provided with a plurality of concentric, oval shaped grooves into which the braided carbon fiber electrodes are mounted.

Detailed Description Text - DETX (4):

The lead of FIG. 1 is provided with four separate carbon fiber electrodes 14, 16, 18 and 20. Each of these electrodes takes the form of tubular braid of metallized carbon fibers, each laid in one of the oval shaped, concentric grooves in electrode pad 10. Each of the carbon fiber electrodes 14, 16, 18 and 20 is provided with an inner tubular core of silicone rubber, around which the tubular braid of carbon fibers is mounted. The carbon fibers are retained within the grooves in base pad 10 by means of medical adhesive, which bonds the tubular core within the carbon fiber braids to the pad 10.

Detailed Description Text - DETX (6):

FIG. 2 is a diagram of an alternate embodiment of a lead employing the present invention. It too is provided with an electrode pad 110 which corresponds to pad 10 in FIG. 1. Pad 110 is similarly provided with a dacron enforcement mesh 112 around its external periphery. In the electrode FIG. 2, only one carbon fiber electrode 114 is provided, mounted to the grooves within pad 110 to provide a spiral shaped electrode. On exiting the electrode pad, electrode 114 is provided with a insulative sheath 112 which extends to the proximal end of the lead.

Detailed Description Text - DETX (9):

FIG. 5 is an illustration of yet another embodiment of an electrode according to the present invention, in which the weaving techniques employed to produce bifurcated tubular structures in the context vascular grafts have been applied to the context of implantable defibrillation leads. As illustrated, a single, large diameter tubular carbon fiber braid 430 is split into two smaller segments and then split again to form four parallel tubular segments 414, 416, 418 and 420. Mounted within segments 414, 416, 418 and 420 are silicone rubber or other plastic core members. The tubular carbon fiber braid may be backfilled with silicone rubber in other areas, in order to prevent tissue ingrowth into the braid in the areas of the bifurcations. The large diameter braid 430 is covered with an insulative sheath 422, extending to the proximal end of the lead, at which point an electrical connector is mounted to braid 430. As illustrated, the carbon fiber electrode structure is mounted to a flexible, insulative backing member 410, which may be provided with grooves corresponding to the desired configuration of the carbon fiber electrode. As in the embodiments illustrated in FIGS. 1 and 2, the carbon fiber electrode may be retained within the grooves by means of silicone rubber medical adhesive. Alternatively, the backing member 410 may be dispensed with, and the electrode used without a backing member, either subcutaneously or epicardially in a manner analogous to the electrode illustrated in FIG. 3.

EAST Browser - L43: (124) 41 and grooves! | US 6217610 | Tag: S | Doc: 13/124 (SORTED) | "Full" 8/36 (Total Images 36) | Drawings

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image D
1	US 3490438 A		USOCR	19700120	8	US 3490
2	US 4217665 A		USPAT	19800819	5	US 4217
3	US 5186711 A		USPAT	19930216	14	US 5186
4	US 5337754 A		USPAT	19940816	15	US 5337
5	US 5350388 A		USPAT	19940927	13	US 5350
6	US 5824038 A		USPAT	19981020	6	US 5824
7	US 5954057 A		USPAT	19990921	30	US 5954
8	US 6045497 A		USPAT	20000404	28	US 6045
9	US 6102943 A		USPAT	20000815	12	US 6102
10	US 6117067 A		USPAT	20000912	11	US 6117
11	US 6167605 B1		USPAT	20010102	8	US 6167
12	US 6214036 B1		USPAT	20010410	16	US 6214
13	US 6217610 B1		USPAT	20010417	36	US 6217
14	US 6261222 B1		USPAT	20010717	25	US 6261
15	US 6260552 B1		USPAT	20010717	49	US 6260
16	US 20010010018 A1		US-PGP	20010726	19	US 2001
17	US 6280466 B1		USPAT	20010828	40	US 6280
18	US 6287250 B1		USPAT	20010911	11	US 6287
19	US 20010021874 A1		US-PGP	20010913	33	US 2001
20	US 20010023311 A1		US-PGP	20010920	16	US 2001
21	US 6296660 B1		USPAT	20011002	28	US 6296
22	US 20010044568 A1		US-PGP	20011122	18	US 2001
23	US 6334446 B1		USPAT	20020101	45	US 6334
24	US 20020016628 A1		US-PGP	20020207	19	US 2002
25	US 6350279 B1		USPAT	20020226	11	US 6350
26	US 20020032482 A1		US-PGP	20020314	19	US 2002
27	US 20020038140 A1		US-PGP	20020328	12	US 2002
28	US 6371979 B1		USPAT	20020416		
29	US 20020052642 A1		US-PGP	20020502		
30	US 20020050277 A1		US-PGP	20020502		
31	US 20020058856 A1		US-PGP	20020516		
32	US 6391054 B1		USPAT	20020521		
33	US 20020068850 A1		US-PGP	20020606		
34	US 6402781 B1		USPAT	20020611		
35	US 6406492 B1		USPAT	20020618		
36	US 6406420 B1		USPAT	20020618		
37	US 20020091300 A1		US-PGP	20020711		
38	US 6419696 B1		USPAT	20020716		
39	US 20020095067 A1		US-PGP	20020718		
40	US 20020095064 A1		US-PGP	20020718		
41	US 20020099259 A1		US-PGP	20020725		
42	US 20020103533 A1		US-PGP	20020801		
43	US 20020103532 A1		US-PGP	20020801		



FIG. 6

EAST Browser - L44: (72) 41 and groov... | US 20020038140 | Tag: S | Doc: 26/72 (SORTED) | "Full" 6/12 (Total images 12) | Drawings

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image D
1	US 4217665 A		USPAT	19800819	5	US 4217
2	US 5186711 A		USPAT	19930216	14	US 5186
3	US 5337754 A		USPAT	19940816	15	US 5337
4	US 5350388 A		USPAT	19940927	13	US 5350
5	US 5824038 A		USPAT	19981020	6	US 5824
6	US 5954057 A		USPAT	19990921	30	US 5954
7	US 6045497 A		USPAT	20000404	28	US 6045
8	US 6102943 A		USPAT	20000815	12	US 6102
9	US 6117067 A		USPAT	20000912	11	US 6117
10	US 6167605 B1		USPAT	20010102	8	US 6167
11	US 6214036 B1		USPAT	20010410	16	US 6214
12	US 6217610 B1		USPAT	20010417	36	US 6217
13	US 6261222 B1		USPAT	20010717	25	US 6261
14	US 6260552 B1		USPAT	20010717	49	US 6260
15	US 20010010018 A1		US-PGP	20010726	19	US 2001
16	US 6280466 B1		USPAT	20010828	40	US 6280
17	US 6287250 B1		USPAT	20010911	11	US 6287
18	US 20010021874 A1		US-PGP	20010913	33	US 2001
19	US 20010023311 A1		US-PGP	20010920	16	US 2001
20	US 6296660 B1		USPAT	20011002	28	US 6296
21	US 20010044568 A1		US-PGP	20011122	18	US 2001
22	US 6334446 B1		USPAT	20020101	45	US 6334
23	US 20020016628 A1		US-PGP	20020207	19	US 2002
24	US 6350279 B1		USPAT	20020226	11	US 6350
25	US 20020032482 A1		US-PGP	20020314	19	US 2002
26	US 20020038140 A1		US-PGP	20020328	12	US 2002
27	US 6371979 B1		USPAT	20020416	15	US 6371
28	US 20020052642 A1		US-PGP	20020502	22	US 2002
29	US 20020050277 A1		US-PGP	20020502	42	US 2002
30	US 20020058856 A1		US-PGP	20020516	34	US 2002
31	US 6391054 B1		USPAT	20020521	34	US 6391
32	US 6402781 B1		USPAT	20020611	21	US 6402
33	US 6406492 B1		USPAT	20020618	9	US 6406
34	US 6406420 B1		USPAT	20020618	45	US 6406
35	US 20020091300 A1		US-PGP	20020711	34	US 2002
36	US 6419696 B1		USPAT	20020716	24	US 6419
37	US 20020095064 A1		US-PGP	20020718	42	US 2002
38	US 20020111533 A1		US-PGP	20020815	31	US 2002
39	US 6447540 B1		USPAT	20020910	17	US 6447
40	US 6464629 B1		USPAT	20021015	40	US 6464
41	US 20020161277 A1		US-PGP	20021031	36	US 2002
42	US 6475136 B1		USPAT	20021105	26	US 6475
43	US 20020169360 A1		US-PGP	20021114	30	US 2002



FIG. 8



FIG. 10



FIG. 7



FIG. 9

EAST Browser - L13: (46) ("3304557" |... | US 3304557 | Tag: S | Doc: 1/46 (SORTED) | "Full" 1/7 (Total Images 7) | Drawings

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Dat	Pages	I
1	US 3304557 A		USPAT	19670221	7	U
2	US 3304557 A		USOCR	19670221	7	U
3	US 3316557 A		USPAT	19670502	7	U
4	US 3316557 A		USOCR	19670502	7	U
5	US 3945052 A		USPAT	19760323	5	U
6	US 4299015 A		USPAT	19811110	8	U
7	US 4652263 A		USPAT	19870324	7	U
8	US 4731073 A		USPAT	19880315	11	U
9	US 4834755 A		USPAT	19890530	11	U
10	US 4922905 A		USPAT	19900508	12	U
11	US 5037377 A		USPAT	19910806	6	U
12	US 5064435 A		USPAT	19911112	9	U
13	US 5084065 A		USPAT	19920128	7	U
14	US 5123917 A		USPAT	19920623	9	U
15	US 5133742 A		USPAT	19920728	11	U
16	US 5163952 A		USPAT	19921117	9	U
17	US 5282847 A		USPAT	19940201	6	U
18	US 5330500 A		USPAT	19940719	8	U
19	US 5387621 A		USPAT	19950207	8	U
20	US 5413598 A		USPAT	19950509	5	U
21	US 5443500 A		USPAT	19950822	6	U
22	US 5443499 A		USPAT	19950822	11	U
23	US 5456713 A		USPAT	19951010	19	U
24	US 5476507 A		USPAT	19951219	12	U
25	US 5496364 A		USPAT	19960305	13	U
26	US 5507770 A		USPAT	19960416	7	U
27	US 5527353 A		USPAT	19960618	7	U
28	US 5545210 A		USPAT	19960813	7	U
29	US 5545209 A		USPAT	19960813	28	U
30	US 5556426 A		USPAT	19960917	11	U
31	US 5556413 A		USPAT	19960917	19	U
32	US 5562727 A		USPAT	19961008	7	U
33	US 5562725 A		USPAT	19961008	10	U
34	US 5591199 A		USPAT	19970107	8	U
35	US 5591195 A		USPAT	19970107	18	U
36	US 5609605 A		USPAT	19970311	8	U
37	US 5617878 A		USPAT	19970408	15	U
38	US 5843158 A		USPAT	19981201	21	U
39	US 6019786 A		USPAT	20000201	19	U
40	US 6336937 B1		USPAT	20020108	27	U
41	US 6409757 B1		USPAT	20020625	10	U
42	US 6592614 B2		USPAT	20030715	20	U
43	US 6733520 B2		USPAT	20040511	13	U



Feb. 21, 1967 S. POLANSKY 3,304,557

SURGICAL PROSTHESIS

Filed Sept. 28, 1965 2 Sheets-Sheet 1

FIG. 1.

FIG. 2.

FIG. 3.

FIG. 4.

FIG. 5.

FIG. 6.

FIG. 7.

INVENTOR.
SEYMOUR POLANSKY

ATTORNEY

EAST Browser - L11: (254) (623/1.24,1.... | US 5609626 | Tag: S | Doc: 59/254 (SORTED) | "Full" 2/12 (Total images 12) | Drawings

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Dat	Pages	Imag
18	US 4050893 A		USPAT	19770927	10	US 4
19	US 4086665 A		USPAT	19780502	6	US 4
20	US 4118806 A		USPAT	19781010	8	US 4
21	US 4183102 A		USPAT	19800115	7	US 4
22	US 4350492 A		USPAT	19820921	6	US 4
23	US 4497074 A		USPAT	19850205	11	US 4
24	US 4592754 A		USPAT	19860603	9	US 4
25	US 4601718 A		USPAT	19860722	20	US 4
26	US 4662885 A		USPAT	19870505	9	US 4
27	US 4705517 A		USPAT	19871110	9	US 4
28	US 4787901 A		USPAT	19881129	9	US 4
29	US 4800603 A		USPAT	19890131	7	US 4
30	US 4828544 A		USPAT	19890509	16	US 4
31	US 4851001 A		USPAT	19890725	9	US 4
32	US 4904254 A		USPAT	19900227	16	US 4
33	US 5089014 A		USPAT	19920218	12	US 5
34	US 5116564 A		USPAT	19920526	9	US 5
35	US 5123919 A		USPAT	19920623	6	US 5
36	US 5139515 A		USPAT	19920818	6	US 5
37	US 5147389 A		USPAT	19920915	16	US 5
38	US 5151105 A		USPAT	19920929	11	US 5
39	US 5156620 A		USPAT	19921020	17	US 5
40	US 5171261 A		USPAT	19921215	7	US 5
41	US 5178634 A		USPAT	19930112	7	US 5
42	US 5197979 A		USPAT	19930330	10	US 5
43	US 5314468 A		USPAT	19940524	8	US 5
44	US 5330528 A		USPAT	19940719	9	US 5
45	US 5358518 A		USPAT	19941025	4	US 5
46	US 5370691 A		USPAT	19941206	6	US 5
47	US 5370684 A		USPAT	19941206	12	US 5
48	US 5376112 A		USPAT	19941227	13	US 5
49	US 5397351 A		USPAT	19950314	11	US 5
50	US 5413599 A		USPAT	19950509	8	US 5
51	US 5423851 A		USPAT	19950613	7	US 5
52	US 5476516 A		USPAT	19951219	6	US 5
53	US 5476471 A		USPAT	19951219	10	US 5
54	US 5500014 A		USPAT	19960319	17	US 5
55	US 5534024 A		USPAT	19960709	7	US 5
56	US 5545215 A		USPAT	19960813	12	US 5
57	US 5554180 A		USPAT	19960910	5	US 5
58	US 5607465 A		USPAT	19970304	7	US 5
59	US 5609626 A		USPAT	19970311	12	US 5
60	US 5609598 A		USPAT	19970311	14	US 5



EAST Browser - L10: (120) 9 and (groov... | US 20030120331 | Tag: S | Doc: 75/120 (SORTED) | "Full" 1/30 (Total images 30) | Front Page

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image D
55	US 20020123788 A1		US-PGP	20020905		
56	US 6461320 B1		USPAT	20021008		
57	US 6468301 B1		USPAT	20021022		
58	US 20020165603 A1		US-PGP	20021107		
59	US 20020169497 A1		US-PGP	20021114		
60	US 20020169496 A1		US-PGP	20021114	19	US 2002
61	US 6482227 B1		USPAT	20021119	27	US 6482
62	US 20020198588 A1		US-PGP	20021226	20	US 2002
63	US 20030004562 A1		US-PGP	20030102		
64	US 20030023300 A1		US-PGP	20030130		
65	US 20030023299 A1		US-PGP	20030130		
66	US 6514283 B2		USPAT	20030204		
67	US 6517572 B2		USPAT	20030211	39	US 6517
68	US 20030065377 A1		US-PGP	20030403		
69	US 6547814 B2		USPAT	20030415		
70	US 20030074049 A1		US-PGP	20030417		
71	US 6551350 B1		USPAT	20030422		
72	US 6554858 B2		USPAT	20030429		
73	US 20030105510 A1		US-PGP	20030605		
74	US 20030114913 A1		US-PGP	20030619		
75	US 20030120331 A1		US-PGP	20030626	30	US 2003
76	US 20030125797 A1		US-PGP	20030703	45	US 2003
77	US 6589273 B1		USPAT	20030708		
78	US 20030130720 A1		US-PGP	20030710	25	US 2003
79	US 20030135261 A1		US-PGP	20030717	41	US 2003
80	US 20030153974 A1		US-PGP	20030814		
81	US 20030181969 A1		US-PGP	20030925	41	US 2003
82	US 6626938 B1		USPAT	20030930	27	US 6626
83	US 20030204241 A1		US-PGP	20031030		
84	US 6645242 B1		USPAT	20031111		
85	US 6645241 B1		USPAT	20031111		
86	US 20030216803 A1		US-PGP	20031120		
87	US 20030216802 A1		US-PGP	20031120		
88	US 6652571 B1		USPAT	20031125		
89	US 6652541 B1		USPAT	20031125	33	US 6652
90	US 6656215 B1		USPAT	20031202	26	US 6656
91	US 6663662 B2		USPAT	20031216		
92	US 6673102 B1		USPAT	20040106	27	US 6673
93	US 20040030218 A1		US-PGP	20040212		
94	US 20040039436 A1		US-PGP	20040226		
95	US 6702802 B1		USPAT	20040309	30	US 6702
96	US 20040049259 A1		US-PGP	20040311		
97	US 6719781 B1		USPAT	20040413	61	US 6719

US 20030120331A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2003/0120331 A1

Chobotov et al. (43) Pub. Date: Jun. 26, 2003

(54) ADVANCED ENDOVASCULAR GRAFT

(75) Inventors: Michael V. Chobotov, Santa Rosa, CA (US); Brian Glynn, Santa Rosa, CA (US); Stuart Karl Windsor, CA (US); Maurice Marthaler, Santa Rosa, CA (US); Robert Whirley, Santa Rosa, CA (US); Isaac Zacharias, Santa Rosa, CA (US)

Correspondence Address:
TOWNSEND AND TOWNSEND AND CREW, LLP
TWO EMBARCADERO CENTER
EIGHTH FLOOR
SAN FRANCISCO, CA 94111-3834 (US)

(73) Assignee: TriVascular, Inc.

(21) Appl. No.: 10/029,559

(22) Filed: Dec. 20, 2001

Publication Classification

(51) Int. Cl.[7] A61F 2/06

(52) U.S. Cl. 623/1.13; 623/1.25; 623/1.36

(57) ABSTRACT

This invention is a system for the treatment of body passageways, in particular, vessels with vascular disease. The system includes an endovascular graft with a low-profile delivery configuration and a deployed configuration in which it conforms to the morphology of the vessel or body passageway to be treated as well as various connector members and stents. The graft is made from an inflatable graft body section and may be bifurcated. One or more inflatable cuffs may be disposed at either end of the graft body section. At least one inflatable channel is disposed between and in fluid communication with the inflatable cuffs.



EAST Browser - L11: (33) 9 and (grooves) | US 20030120331 A1 | Tag: S | Doc: 18/33 (SORTED) | Format : KWIC

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image Doc
1	US 5628786 A		USPAT	19970513	10	US 56287
2	US 5873904 A		USPAT	19990223	24	US 58739
3	US 6077217 A		USPAT	20000620	14	US 60772
4	US 6159239 A		USPAT	20001212	41	US 61592
5	US 6267783 B1		USPAT	20010731	15	US 62677
6	US 20010053930 A1		US-PGP	20011220	41	US 20010
7	US 20020035395 A1		US-PGP	20020321	26	US 20020
8	US 20020058993 A1		US-PGP	20020516	37	US 20020
9	US 20020058987 A1		US-PGP	20020516	33	US 20020
10	US 20020058986 A1		US-PGP	20020516	33	US 20020
11	US 20020058985 A1		US-PGP	20020516	22	US 20020
12	US 20020058984 A1		US-PGP	20020516	28	US 20020
13	US 6428550 B1		USPAT	20020806	34	US 64285
14	US 20020169496 A1		US-PGP	20021114	19	US 20020
15	US 6482227 B1		USPAT	20021119	27	US 64822
16	US 20020198588 A1		US-PGP	20021226	28	US 20020
17	US 6517572 B2		USPAT	20030211	39	US 65175
18	US 20030120331 A1		US-PGP	20030626	30	US 20030
19	US 20030125797 A1		US-PGP	20030703	45	US 20030
20	US 20030130720 A1		US-PGP	20030710	25	US 20030
21	US 20030135261 A1		US-PGP	20030717	41	US 20030
22	US 20030181969 A1		US-PGP	20030925	41	US 20030
23	US 6626938 B1		USPAT	20030930	27	US 66269
24	US 6652541 B1		USPAT	20031125	33	US 66525
25	US 6656215 B1		USPAT	20031202	26	US 66562
26	US 6673102 B1		USPAT	20040106	27	US 66731
27	US 6702802 B1		USPAT	20040309	30	US 67028
28	US 6719781 B1		USPAT	20040413	61	US 67197
29	US 20040098092 A1		US-PGP	20040520	25	US 20040
30	US 20040106980 A1		US-PGP	20040603	23	US 20040
31	US 6805706 B2		USPAT	20041019	24	US 68057
32	US 20040225346 A1		US-PGP	20041111	43	US 20040
33	US 20050055079 A1		US-PGP	20050310	16	US 20050

DOCUMENT-IDENTIFIER: US 20030120331 A1

TITLE: Advanced endovascular graft

---------- KWIC ---------

Current US Classification, US Primary
Class/Subclass - OCPR (1):
623/1.13

Summary of Invention Paragraph - BSTX (18):
[0017] In addition, the stent may comprise grooves. In a typical delivery system, some type of belts or sutures may be used to help retain the endovascular graft in its compressed delivery configuration. The grooves may accommodate these belts or sutures without increasing the small diameter delivery of the device.

Detail Description Paragraph - DETX (29):
[0083] During preparation of graft 10 (and therefore proximal stent 40) into its reduced diameter delivery configuration, each barb 43 is placed behind a corresponding strut 41 (and optional tuck pad 45, if present) so to thereby prevent that barb from contacting the inside of a delivery sheath or catheter during delivery of the device and from undesired contact with the inside of a vessel wall. As described in copending U.S. patent application Ser. No. 09/917,371 to Chobotov et al., a release belt disposed in one or more grooves 35 disposed on struts 41 retain proximal stent 40 in this delivery configuration.

Detail Description Paragraph - DETX (38):
[0092] Proximal stent 70 also may comprise one or more sets of optional grooves 87 for housing device release bands as previously discussed.

EAST Browser - L11: (33) 9 and (grooves) | US 20030120331 | Tag: S | Doc: 18/33 (SORTED) | "Full" 6/30 (Total images 30) | Drawings

File Edit View Tools Window Help

	Document ID	Kind Code	Source	Issue Date	Pages	Image Doc
1	US 5628786 A		USPAT	19970513	10	US 562878
2	US 5873904 A		USPAT	19990223	24	US 587390
3	US 6077217 A		USPAT	20000620	14	US 607721
4	US 6159239 A		USPAT	20001212	41	US 615923
5	US 6267783 B1		USPAT	20010731	15	US 626778
6	US 20010053930 A1		US-PGP	20011220	41	US 200109
7	US 20020035395 A1		US-PGP	20020321	26	US 200203
8	US 20020058993 A1		US-PGP	20020516	37	US 200205
9	US 20020058987 A1		US-PGP	20020516	33	US 200205
10	US 20020058986 A1		US-PGP	20020516	33	US 200205
11	US 20020058985 A1		US-PGP	20020516	22	US 200205
12	US 20020058984 A1		US-PGP	20020516	28	US 200205
13	US 6428550 B1		USPAT	20020806	34	US 642855
14	US 20020169496 A1		US-PGP	20021114	19	US 200203
15	US 6482227 B1		USPAT	20021119	27	US 648222
16	US 20020198568 A1		US-PGP	20021226	28	US 200203
17	US 6517572 B2		USPAT	20030211	39	US 651757
18	US 20030120331 A1		US-PGP	20030626	30	US 200301
19	US 20030125797 A1		US-PGP	20030703	45	US 200301
20	US 20030130720 A1		US-PGP	20030710	25	US 200301
21	US 20030135261 A1		US-PGP	20030717	41	US 200301
22	US 20030181969 A1		US-PGP	20030925	41	US 200301
23	US 6626938 B1		USPAT	20030930	27	US 662693
24	US 6652541 B1		USPAT	20031125	33	US 665254
25	US 6656215 B1		USPAT	20031202	26	US 665621
26	US 6673102 B1		USPAT	20040106	27	US 667310
27	US 6702802 B1		USPAT	20040309	30	US 670280
28	US 6719781 B1		USPAT	20040413	61	US 671978
29	US 20040098092 A1		US-PGP	20040520	25	US 200401
30	US 20040106980 A1		US-PGP	20040603	23	US 200401
31	US 6805706 B2		USPAT	20041019	24	US 680570
32	US 20040225346 A1		US-PGP	20041111	43	US 200402
33	US 20050055079 A1		US-PGP	20050310	16	US 200501



FIG. 4